



GUOWEI GUILLOTINE 92.F



CE conformity - Width 92 cm, max depth 93 cm, max. Cutting height 13 cm - Speed 45 cuts/mn
 Japan alternative digital servo control technology; 15-inch colourful touching LCD.
 The data resolution rate is 0.01mm. It has self-diagnostic function of troubles and displays
 And has 100 program units, over 10000 different cutting positions,
 dynamic display of cutting and running, dynamic tracking, max feeding speed 8-20m/min.
 Powerful computer operating system with more functions - it can store and memorize things.
 The storage time can be up to 300,000 hours with self-maintenance of the operating system.
 Hydraulic components from Italy. Linear double guide rails, PLC control system are adopted to monitor
 all mechanical implementation. Its key parts adopt imported bearing of low maintenance.

Model / Spécifications	92.F
<i>Cutting width</i> / Largeur de coupe (cm)	92
<i>Max. cutting height</i> / Hauteur de pile (cm)	13
<i>Max. cutting depth</i> / Profondeur maxi (cm)	93
<i>Min cutting depth</i> / Minimum de coupe (cm)	2,3
<i>Extended length of working table</i> / Tables de travail latérales (cm)	65x2
<i>Height of working table</i> / Hauteur de la table (cm)	86-90
<i>Width including side working table</i> / Largeur tables frontales (cm)	233
<i>Length of working table</i> / Longueur table centrale (cm)	198
<i>Cutting speed</i> / Vitesse de coupe (mn)	45
<i>Max. Paper pressure</i> / Pression maxi (tonnes)	35
<i>Power of main motor</i> / Moteur principal (kWh)	3
<i>Motor for paper feeding</i> / Moteur équerre (kWh)	0,75
<i>Air pump</i> / Compresseur (kWh)	0,55
<i>Machine weight</i> / Poids (kg)	2800
<i>Length x width x height</i> / Longueur x largeur x Haut (cm)	228x195x140

Name / Composition	Brand model / Marques	Origin
<i>Computer display screen</i> / Écran tactile	WEINVIEW 15 inches color touch screen	Taiwan
<i>Ball-lead screw</i> / Roulement à bille	ABBA / ABBA Ball-lead screw	Taiwan
<i>Linear guide</i> / Bande millimétrée	ABBA High-precision linear guide	Taiwan
<i>Control center</i> / Contrôle central	Panasonic PLC	Japan
Servo drive	Panasonic servo drive	Japan
Servo motor	Panasonic servo motor	Japan
<i>IR Grating</i> / Réseau		Italy
<i>Overload protection switch</i> / Contrôle pression	Schneider	France
<i>Relays</i> / Relais	IDEC	Japan
<i>Contacteur</i> / Contacteur DRT	LS	Korean
<i>Air switch</i> / Bouton d'air	LS	Korean
<i>Start button</i> / Mise en service	Moeller	Germany
<i>Locating switch</i> / Molette de positionnement	Schneider	France
<i>Hydraulic Pum</i> / Pompe	Marzocchi/Brevini	Italy
<i>Hydraulic solenoid valve</i> / Electrovanne	Hyde Fuchs	American
<i>Worm Reducer</i> / Réducteur	CEM	American
<i>Proximity Switch</i> / Interrupteur	FOTEK	Taiwan
<i>Bearing</i> / Pignons	NSK	Japan
<i>Knife</i> / Lame	IKS	Shanghai
<i>Safety Relays</i> / Barrières cellules	LEUZE	Germany

Non-contractual document

ETS JACQUES CHAILLOU

59, avenue Jacques-Cœur - F.18140 LA CHAPELLE-MONTLINARD
 ● Tél. 332.48.79.45.80 ● Fax 332.48.79.45.81 ● info@jacqueschailou.com